



ADMINISTRATIVE RULES OF MONTANA



4.12.736 SYSTEMS MOUNTED ON VEHICLES AND IMPLEMENTS OF HUSBANDRY FOR THE APPLICATION OF NITROGEN FERTILIZER SOLUTIONS

- (1) Working pressure and classifications of containers. Containers shall be constructed in accordance with ARM 4.12.725.
- (2) Mounting of containers shall be as follows:
 - (a) Each container shall be supported so as to prevent the concentration of excessive loads on the supporting portion of the shell.
 - (b) A hold-down device shall be provided which will anchor container to vehicle at one or more places on each side.
 - (c) When the cradle and the tank are of dissimilar metals, material which will not deteriorate with weather or create friction shall be used between to eliminate metal-to-metal contact.
- (3) Container, valves and accessories:
 - (a) Each container shall be equipped with a liquid level gauging device.
 - (b) Flow control equipment may be connected directly to the tank coupling or flange, in which case a flexible connection shall be used between such control equipment and the remainder of the liquid withdrawal system. Flow control equipment not so installed may be connected to the container with a flexible connection.

Authorizing statute(s): Sec. 80-10-503, MCA

Implementing statute(s): Sec. 80-10-503, MCA

History: NEW, 1986 p. 1820, Eff. 10/31/86.